

Xcolor Poster LED

Xcolor
鑫巨彩

深圳市鑫巨彩开发技术有限公司

SHENZHEN XCOLOR LED CO.,LTD

Xcolor Poster LED

- Customizable size
- Iron, die-cast aluminum
- Multiple installation methods
- Suitable for indoor and outdoor poster screens
- Compatible with P1.53, P1.667, P1.86, P2, P2.5,P3.076, P4, P5, P6.67, P8
- Can be seamlessly spliced and multi-screen playback



Xcolor

Poster LED

TYPE OPTIONAL



INDOOR IRON CABINET



OUTDOOR IRON CABINET

- The cabinet size can be customized according to the module size




640*1920mm



960*1920mm




Brightness
adjustable



Seamless
splicing



High definition
contrast



Wide Angle



Looping




Low Energy
consumption

Xcolor Poster LED

DIMENSION & WEIGHT



- ◆Cabinet Dimension
640mm*1920mm (regular)
- ◆Cabinet Weight
38.6kg
- ◆IP Protection
IP45 / IP65



Xcolor

Poster LED

HANDLE OPTION



Xcolor

Poster LED

CONTROL METHOD



When place order, please tell us how will you install the poster led display, then we will provide you different installation accessories.



Diagonal brace



Standing



Hoisting



Creative installation



◆ Use alone or seamlessly splice



◆ Multi-screen playback



TECHNICAL PARAMETERS

Pitch	P1.53	P1.667	P1.86	P2	P2.5	P3.076	P4	P5	P6.67	P8
LED Configuration	SMD1212	SMD1212	SMD1515	SMD1515	SMD2121/1415	SMD2121/1415	SMD2121/1921	SMD2121/1921/2525	SMD3535	SMD3535
Cabinet size	640 × 1920mm	640 × 1920mm	640 × 1920mm	640 × 1920mm	640 × 1920mm	640 × 1920mm	640 × 1920mm	640 × 1920mm	640 × 1920mm	640 × 1920mm
Module size	320 × 160mm	320 × 160mm	320 × 160mm	320 × 160mm	320 × 160mm	320 × 160mm	320 × 160mm	320 × 160mm	320 × 160mm	320 × 160mm
Density	424531dot/m ²	360000dot/m ²	288906dot/m ²	250000dot/m ²	160000dot/m ²	105625dot/m ²	62500dot/m ²	40000dot/m ²	22500dot/m ²	15625dot/m ²
Resolution/cabinet	418 × 1248	384 × 1152	344 × 1032	320 × 960	256 × 768	208 × 624	160 × 480	128 × 384	96 × 288	80 × 240
Resolution/module	209 × 104	192 × 96	172 × 86	160 × 80	128 × 64	104 × 52	80 × 40	64 × 32	48 × 24	40 × 20
Scan mode	52s	48s	43s	40s	32s	32s	20s	16s/8s	6s	5s
Brightness	indoor 500 ~ 900cd/m ²	indoor 500 ~ 900cd/m ²	indoor 500 ~ 900cd/m ²	indoor 800 ~ 1100cd/m ²	indoor 800 ~ 1100cd/m ² outdoor 3500cd/m ²	indoor 800 ~ 1100cd/m ² outdoor 3500cd/m ²	indoor 800 ~ 1100cd/m ² outdoor 4500cd/m ²	indoor 800 ~ 1100cd/m ² outdoor 4500cd/m ²	outdoor 4500cd/m ²	outdoor 5000cd/m ²
Gray Level	16bits	16bits	16bits	16bits	16bits	16bits	16bits	16bits	16bits	16bits
Refresh rate	≥1920hz	≥1920hz	≥1920hz	≥1920hz	≥1920hz	≥1920hz	≥1920hz	≥1920hz	≥1920hz	≥1920hz
Cabinet weight/kg	38.6kg	38.6kg	38.6kg	38.6kg	38.6kg	38.6kg	38.6kg	38.6kg	38.6kg	38.6kg
Max.-Ave Power Co.(W/m ²)	800/240	800/240	800/240	800/240	800/240	800/240	800/240	800/240	800/240	800/240
Temperature range	-20 ~ + 55℃	-20 ~ + 55℃	-20 ~ + 55℃	-20 ~ + 55℃	-20 ~ + 55℃	-20 ~ + 55℃	-20 ~ + 55℃	-20 ~ + 55℃	-20 ~ + 55℃	-20 ~ + 55℃
IP Protection	IP45	IP45	IP45	IP35	IP35/IP65	IP35/IP65	IP35/IP65	IP35/IP65	IP65	IP65



微 信 公 众 号



Email:sales@szxcolorled.com

<http://www.szxcolor.com>

ADD:The 2nd floor, building 1, Changxin high tech
industrial park,
Sha yi wan an road, Shajing street, Bao'an District,
Shenzhen.

